





浙江嘉善远东滚针轴承

YUANDONG PIN-BEARING FACTORY IN JIASHAN ZHEJIANG PROVINCE


68系列




开放型



单边防尘盖 (Z)



双边防尘盖 (ZZ)



单边密封圈 (NSL)



双边密封圈 (2NSL)

轴承号 Bearing Number	孔径	外径	宽度	倒角	钢球 Iron shot		额定负荷(KN) Load Rating (KN)	
	Bore d mm inch	Outer diameter d mm inch	Width B mm inch	Radius R min mm inch	Size mm	Quantity N°	Dynamic Cr	Static Cor
686	6.2362	13.5118	3.5.1968	0.2.008	2.0	8	0.83	0.39
687	7.2756	14.5512	3.5.1968	0.2.008	2.0	9	0.90	0.44
688	8.3150	16.6300	4.1968	0.3.012	2.0	10	0.97	0.50
689	9.3543	17.6693	4.1968	0.3.012	2.0	11	1.02	0.54
61800	10.3937	19.7480	5.1969	0.3.012	2.381	9	1.23	0.63
61801	12.4724	21.8628	5.1969	0.3.012	2.381	12	1.47	0.84
61802	15.5906	24.9449	5.1969	0.3.012	2.381	14	1.59	0.98
61803	17.6693	26.10236	5.1969	0.3.012	2.381	15	1.64	1.05
61804	20.7874	32.1.2598	7.2756	0.3.012	3.175	14	2.67	1.74
61805	25.9843	37.1.4567	7.2756	0.3.012	3.175	16	2.82	1.98
61806	30.1.1811	42.1.6535	7.2756	0.5.020	3.175	19	3.94	2.23
61807	35.1.3780	47.1.8504	7.2756	0.5.020	3.175	22	3.32	2.73
61808	40.1.5748	52.2.0472	7.2756	0.5.020	3.175	24	3.43	2.98
61809	45.1.7716	58.2.2835	7.2756	0.6.024	3.175	27	5.77	4.46
61810	50.1.9685	65.2.5590	7.2756	0.6.024	3.969	24	5.08	4.65
61811	55.2.1654	72.2.8346	9.3543	0.6.024	4.7625	21	6.88	6.14
61812	60.2.3622	78.3.0709	10.3937	0.6.024	4.7625	23	8.85	8.15
61813	65.2.559	85.3.346	10.3937	0.6.024	4.7625	26	9.23	8.85
61814	70.2.756	90.3.543	10.3937	0.6.024	4.7625	28	9.30	9.15
61815	75.2.953	95.3.740	10.3937	0.6.024	4.7625	30	9.62	9.85
61816	80.3.150	100.3.397	10.3937	0.6.024	4.7625	31	9.77	10.23