



16系列

轴承型号 Bearing Number			外径 Bore	外径 O.D	宽度 Width	倒角(最小) Radius(min)	钢球 Lron shot		额定负荷(KN) Load Rating (KN)	
形式 Open	双面防尘盖 Double shield	双面密封圈 Double seal	d mm	D mm	开式/闭式 Open/closed	R mm	数量 Quantity	尺寸 Dimension	动 Move	静 Motionless
1601	1601ZZ	1601 2RS	4.762	17.462	6.35/6.35	0.3	6	3.175	1.98	0.74
			4.762	17.462	7.938/7.938	0.3	6	3.175	2.26	0.84
1602	1602ZZ	1602 2RS	6.350	17.462	6.35/6.35	0.3	6	3.175	1.98	0.74
			6.350	17.462	7.938/7.938	0.3	6	3.175	2.26	0.84
1603	1603ZZ	1603 2RS	7.938	22.225	7.144/7.144	0.3	7	3.969	3.31	1.38
			7.938	22.225	8.731/8.731	0.3	7	3.969	3.32	1.38
1604	1604ZZ	1604 2RS	9.525	22.225	7.144/7.144	0.3	7	3.969	3.33	1.41
		1605 2RS	9.525	22.225	8.731/8.731	0.3	7	3.969	3.32	1.38
1605	1605ZZ	1606 2RS	7.938	23.019	7.938/7.938	0.3	7	3.969	3.31	1.38
1606	1606ZZ	1607 2RS	9.525	23.019	7.938/7.938	0.3	7	3.969	3.33	1.41
1607	1607ZZ	1614 2RS	11.112	23.019	7.938/7.938	0.3	9	3.175	2.70	1.27
1614	1614ZZ	1615 2RS	9.525	28.575	9.525/9.525	0.3	8	4.762	5.12	2.40
1615	1615ZZ	1616 2RS	11.112	28.575	9.525/9.525	0.3	8	4.762	5.12	2.40
1616	1616ZZ	1620 2RS	12.700	28.575	9.525/9.525	0.3	8	4.762	5.12	2.40
1620	1620ZZ	1621 2RS	11.112	34.925	11.112/11.112	0.6	7	6.350	7.77	3.61
1621	1621ZZ	1622 2RS	12.700	34.925	11.112/11.112	0.6	7	6.350	7.77	3.61
1622	1622ZZ	1623 2RS	14.288	34.925	11.112/11.112	0.6	7	6.350	7.77	3.61
1623	1623ZZ	1628 2RS	15.875	34.925	11.112/11.112	0.6	7	6.350	7.77	3.61
1628	1628ZZ	1630 2RS	15.875	41.275	12.7/12.7	0.6	8	6.747	9.58	4.81
1630	1630ZZ	1633 2RS	19.050	41.275	12.7/12.7	0.6	9	6.350	9.39	5.08
1633	1633ZZ	1635 2RS	15.875	44.45	12.7/12.7	0.6	7	8.731	12.92	6.22
1635	1635ZZ	1638 2RS	19.05	44.45	12.7/12.7	0.6	7	8.731	12.92	6.22
1638	1638ZZ	1640 2RS	19.05	50.8	14.288/14.288	0.6	10	6.350	10.7	5.81
1640	1640ZZ	1641 2RS	22.225	50.8	14.288/14.288	0.6	10	6.350	10.7	5.81
1641	1641ZZ	99502H	25.400	50.8	12.7/12.7	0.6	10	6.350	10.7	5.81
	77502H		15.875	340.925	11/11	0.5	7	6.350	6.00	3.25